


<p align="center"><b>33 Range</b> Double Sided PVC Foam Tape</p>	<p align="center"><b>Ref: 33 Range</b></p>	
--	--	---

## 1. Product Description / Application

Rev Dec 18

PVC Glazing tape ref 33 range is a high density pvc foam available in black and white. It is really suited to bonding difficult and dissimilar surfaces including metals, wood, upvc and many plastics. The foam construction provides excellent conformability and is therefore ideal for rough, uneven and structured surfaces. In addition the foam offers excellent sealing, dampening and vibration absorption capabilities ensuring that bonded joints remain permanently secure even in critical and exacting applications.

Our 33 range has a good initial tack, combined with its superior bonding characteristics, enabling easy assembly and positioning. This product is therefore, ideal for all permanent fixing and mounting applications of component joints.

## 2. Key Characteristics

- High initial tack
- High shear, high peel, high adhesive mass
- Good affinity to many plastics
- Good temperature resistance
- Available in thicknesses from 1mm to 6mm
- Available in both black and white


## 4. Product Data

<u>Item</u>	<u>Value</u>	<u>Test Method</u>
Density (kg/m <sup>3</sup> )	83	ASTM D1667
Compression Set (%)	14.1	ASTM D395-03
Compression Strength (Kpa)	12.3	ASTM D1667-05
180° Peel Strength (N/25mm, 300mm/min)	27	GB/T 2792-1998
Elongation (%)	156	ASTM D638-03
Elongation Strength (Mpa)	0.38	ASTM D638-03
Temperature Range °C	-20°C to + 100°C	

### Important Notice

*All products are subjected to careful quality control throughout the manufacturing process and are warranted to be of merchantable quality and free from manufacturing defects. Published information concerning products is based upon research, which the Company believes to be reliable, but some information does not constitute a warranty. Because of the variety of possible uses for products and continuing development of new uses, the purchaser should carefully consider the fitness and performance of the product for each intended use and the purchaser assumes all risks in connection with such use. Seller shall not be liable for damages in excess of the purchase price of the product nor for incidental nor consequential damages. All specifications are subject to change without prior notice.*

Tel 01324 610710  
Fax 01324 610888



sales@sealco-scotland.co.uk  
www.sealco-scotland.co.uk