



Designed for:	Attaching hardware to unreinforced PVCU
Head Style:	Countersunk
Drive Bit:	PH2
Thread Form:	Single Deep Thread
Point:	Fast Starting Gimlet Point
Coating:	Electroplated Zinc plus clear or yellow passivation
Salt Spray Testing:	Minimum 250 Hours in accordance with BS EN 9227:2012
Corrosion protection	Grade 4 acc. to BS EN 1670:2007
Shank Material:	Carbon steel
Material Grade:	AISI C1018
Effective Thread Length:	Fully Threaded

Product Code	Size – Shank x NL	HD	Box Quantity
CFG 4.0 x 25 Z	4.0mm x 25.0mm	6.75mm ± 0.25mm	1000
CFG 4.3 x 13 Z	4.3mm x 13.0mm	7.25mm ± 0.25mm	1000
CFG 4.3 x 16 Y or Z	4.3mm x 16.0mm	7.25mm ± 0.25mm	1000
CFG 4.3 x 20 Y or Z	4.3mm x 20.0mm	7.25mm ± 0.25mm	1000
CFG 4.3 x 22 Y or Z	4.3mm x 22.0mm	7.25mm ± 0.25mm	1000
CFG 4.3 x 25 Y or Z	4.3mm x 25.0mm	7.25mm ± 0.25mm	1000
CFG 4.3 x 28 Z	4.3mm x 28.0mm	7.25mm ± 0.25mm	1000
CFG 4.3 x 30 Y or Z	4.3mm x 30.0mm	7.25mm ± 0.25mm	1000
CFG 4.3 x 35 Y or Z	4.3mm x 35.0mm	7.25mm ± 0.25mm	1000
CFG 4.3 x 40 Y or Z	4.3mm x 40.0mm	7.25mm ± 0.25mm	1000
CFG 4.3 x 45 Y or Z	4.3mm x 45.0mm	7.25mm ± 0.25mm	500
CFG 4.3 x 55 Y or Z	4.3mm x 55.0mm	7.25mm ± 0.25mm	500
CFG 4.3 x 65 Y or Z	4.3mm x 65.0mm	7.25mm ± 0.25mm	500.
CFG 4.8 x 25 Y or Z	4.8mm x 25.0mm	7.25mm ± 0.25mm	1000
CFG 4.8 x 38 Y or Z	4.8mm x 38.0mm	7.25mm ± 0.25mm	500



Rapierstar Limited  
Star Business Park, Macclesfield, Cheshire SK11 9JA  
Tel: +44(0)1260 223311 Fax: +44(0)1260 223399  
email: [info@rapierstar.com](mailto:info@rapierstar.com)

[www.rapierstar.com](http://www.rapierstar.com)

