



Designed for:	Attaching Handles to PVCU Window and Door Sashes
Head Style:	Countersunk
Drive Bit:	PH2
Thread Form:	Metric Thread
Point:	B Point to DIN 965
Coating:	Electroplated Zinc plus Passivation
Salt Spray Testing:	Minimum 250 Hours in accordance with BS EN 9227:2012
Corrosion Protection:	Grade 4 acc. to BS EN 1670:2007
Shank Material:	Carbon Steel
Material Grade:	AISI C1008
Effective Thread	Length: Fully Threaded

Product Code	Size – Shank x NL	HD	Box Quantity
MS M5 x 12 Z	5.0mm x 12mm	9.02mm ± 0.18mm	1000
MS M5 x 16 Z	5.0mm x 16mm	9.02mm ± 0.18mm	1000
MS M5 x 20 Z	5.0mm x 20mm	9.02mm ± 0.18mm	1000
MS M5 x 25 Z	5.0mm x 25mm	9.02mm ± 0.18mm	1000
MS M5 x 30 Z	5.0mm x 30mm	9.02mm ± 0.18mm	1000
MS M5 x 35 Z	5.0mm x 35mm	9.02mm ± 0.18mm	1000
MS M5 x 40 Z	5.0mm x 40mm	9.02mm ± 0.18mm	1000
MS M5 x 45 Z	5.0mm x 45mm	9.02mm ± 0.18mm	1000
MS M5 x 50 Z	5.0mm x 50mm	9.02mm ± 0.18mm	1000
MS M5 x 70 Z	5.0mm x 70mm	9.02mm ± 0.18mm	1000



Rapierstar Limited
Star Business Park, Macclesfield, Cheshire SK11 9JA
Tel: +44(0)1260 223311 Fax: +44(0)1260 223399
email: info@rapierstar.com

www.rapierstar.com

